

SBS-4001 PRISMA MAXIMA CAMERA SORTER

THE BELT TYPE MONOCHROMATIC & TRICHROMATIC CCD CAMERA SORTERS

The **SPECTRUM SBS-4001 PRISMA** & the **SBS-4001 MAXIMA** are Monochromatic and Trichromatic CCD Camera based Colour Sorters and are a result of over two decades of R & D at Spectrum industries.

These Belty type Colour Sorters are ideal for sorting brittle products such as Raw & Blanched Peanuts, Cashewnuts, Almonds etc. As well as non-free flowing material such as Raisins, Fresh and Dehydrated Vegetables such as Onion, Garlic, carrot cubes etc.

The **SBS-4001 PRISMA** use advanced digital 2048 pixel CCD Line Scan Cameras that produce a very high resolution image of the object.

The **S-4001 MAXIMA** use advanced 5400 pixel x 3, Tri-linear RGB, CCD Line Scan Cameras to scan the product in the Red, Green and Blue region of light in order to identify even subtle defects in product quality.

The machines have LED Solid State Lighting that provides High Intensity long life stable lightning.

Large Format Lenses with digital automatic LED backlights are employed to ensure highest quality imaging of the product, that is also displayed on a 15" Colour LED TFT screen, for online viewing and monitoring of the product. The resultant data is compared with pre-set parameters, to reject the defective product using ultra-fast, long life, custom designed pneumatic ejectors.

The machines have the ability to detect and reject over 200,000 objects/minute with a defect size of even 0.025mm sq. They are fully computer controlled with automatic calibration and self-check Instant change over from one product sort to another is possible, using pre-stored sorting Algorithms.

TECHNICAL FEATURES

- High Resolution Monochromatic 2048 pixels CCD Cameras or 5400 pixels 3, tri-linear Full Colour CCD Camera
- Monochromatic or Penta-chromatic LED Solid state high intensity long life stable lightning.
- On-line live visual display of product being sorted on 15" Colour LED TFT screen.
- Ultra-fast long life pneumatic ejectors with response time of 1ms and life of up to 5 billion cycles.
- Automatic cleaning of viewing area by wiper system.
- Automatic online calibration with self-check procedures.
- Fully computer controlled

SPECIFICATIONS



FM 70723
ISO 9001:2000 CERTIFIED

Air Requirement	
Pressure	7 Bar(100 PSI)
Consumption	15-50 Ltr/sec(32-110cfm) approximate depending on the rejection rate.
Air Quality	Free of Oil, water and dirt

Electrical Requirement	
Voltage	110/230 V AC Three Phase
Frequency	50/60 Hz
Power	2-5 Kw

Note:

- Available in capacities ranging from 1 to 12 ton per hour.
- In View of Improvements in design, Specifications are subject to change without prior notice.



SPECTRUM INDUSTRIES
success through Innovation

E14, C15 & C16,
Yeyyadi Industrial Estate
Mangalore - 575008,
Karnataka, India.

143 II, Industrial Area,
Balkampady
Mangalore - 575 011,
Karnataka, India.

www.spectrumindustries.net
sales@spectrumindustries.net
Telephone: +91 824 222 1018
Telefax: +91 824 221 4395